Confined Space Program

Office of Environmental Health and Safety

Revised July 2018

Cleveland State University
Confined Space Entry Program

Introduction

Final rules addressing safe entry into confined spaces can be found in 29 CFR 1910.146 (Permit-

6. Establishing measures for unauthorized entry (i.e., restrict access and have employees intercept visitors).

7. Ensuring measures will be taken to remove all conditions making a permitted space unsafe prior to entry (i.e., increasing ventilation, lock-out tagout procedures, using intrinsically-safe equipment.)

8. Coordinating entry of University spaces by Outside contractors.

9. Reviewing training records to verify employees have participated in training programs.

Attendants

Employees with the following job classifications are designated as Attendant's: (Entry Supervisors are authorized as attendants)

Attendant duties include:

1. Ensuring that all monitoring equipment is calibrated and operation prior to use in adherence to manufacturer's recommendations.

2. Ensuring that all entrants are familiar with monitoring procedures prior to entry.

3. Monitoring the atmosphere inside and outside the space the entire time the entrant is in the permitted space when the atmosphere has the potential to become hazardous.

4. Monitoring the initial entry conditions only when risk of a hazardous atmosphere developing is negligible.

5. Maintaining communications with the entrant and rescue services.

6. Performing non-entry rescue if deemed essential (e.g., using a winch to retrieve entrant without breaking the plane).

7. Attending formal Confined Space Entry Program training.

   Notes:

8. Attendants are not permitted to engage in any other duties or tasks which may be a distraction from monitoring the activities of the entrant inside the permitted space, or from observing the conditions outside the space which may become a threat to the entrant.

9. The entrant is never permitted to leave the entrance to the permitted space for any reason unless another trained attendant is present to provide relief.

Pre-

Communication Equipment

Appropriate communication equipment will be provided to the attendant to assure they can maintain contact with entrants and rescue team members. Such equipment may include telephones, radios, pagers, etc…

Body Harness/Retrieval Lines

A full-body safety harness will be worn by all entrants into a permit- required confined space. This harness will be designed to allow easy lifting and/or dragging of incapacitated entrants safety from the space by both shoulders or by a single line connection between the shoulder and the back.

The only instances where wearing a safety harness may be exempted is where the space configuration/construction may actually result in a potential hazard by becoming entangled with equipment or items located within the space. The Program Director alone shall make the determination as to whether this exemption may be granted.

Hoists

A hoisting device shall be provided should the intended space for entry be a manhole, or if the space contains a top/vertical opening. This device shall not be electrical or pneumatic, but rather mechanically operated.
When there is no suitable structure overhead to mount the hoist on, a tripod system shall be placed over the space entrance. This tripod system must be of sufficient strength and height, and constructed so that the entrant may be safely removed from the space, and swung outward.

Ladders

Ladders that meet OSHA specifications shall be used when entering or leaving a manhole, vertical opening, or pit. Use ladders when entering a space from ground level when there is a depth of four feet or more.

Procedures for Rescue

Rescue team members are not permitted to enter a confined space unless an authorized attendant is stationed at the entrance. No rescue team member shall enter a permit-
req ms san

Definitions

The following are some terms applicable to this Confined Space Program. The definitions were taken from the Code of Federal Regulations Title 29 (29 CFR 1910.146):

"Attendant" means an individual stationed outside a permit space who monitors the authorized entrants, and performs all duties of an attendant as assigned by this Confined Space Program.

"Blanking or Blinding" means the absolute closure of a pipe, line, or duct by the fastening of a solid plate that completely covers the bore and is capable of withstanding the maximum pressure of the pipe, line, or duct, with no leakage beyond the plate.

"Calibration" means a laboratory or bench-top resetting of alarm points and zeros, in accordance with manufacturer's specifications. Calibration shall be conducted by the manufacturer, or by a trained company representative.

"Class I, Division I Location" means a location in which (1) ignitable concentrations of flammable gases or vapors can exist under normal operating conditions; or (2) ignitable concentrations of such gases or vapors can exist frequently due to repair or maintenance operations or due to leakage; or (3) breakdown of faulty operation equipment or processes might release ignitable concentrations of flammable gases or vapors and might also cause simultaneous failure of electrical equipment.

"Class II, Division I Location" means a location in which (1) combustible dust in the air under normal operating conditions in quantities and sufficient to produce explosive or ignitable mixtures; or (2) mechanical failure or abnormal operation of machinery or equipment might cause such explosive or ignitable mixtures to be produced, and might also provide a source of ignition through simultaneous failure of electrical equipment, operation of protection devices, or from other causes, or (3) combustible dusts or an electrically conductive nature may be present in hazardous quantities.

"Confined Space" means any space that:

1. Is large enough and configured such that an employee can bodily enter and perform assigned work;
2. has limited means of entry/egress (for example, tanks, vessels, silos, storage bins, hoppers, vaults, boilers, sewers, manholes, ventilation or exhaust ducts, and pits are some spaces that may have limited means of entry.); and
3. is not designed for continuous human occupancy

4. Airborne combustible dust at a concentration that meets or exceeds its LEL, e.g., approximated where dust obscures vision at a distance of five feet or less;
5. Any other atmospheric condition defined as immediately dangerous to life or health as defined in this section.

"Immediately Dangerous to Life or Health (IDLH)" means any condition that poses an immediate or delayed threat to life or that would cause irreversible adverse health effects or that would interfere with an individual's ability to escape unaided from a permit space.

"Inerting" means the displacement of the atmosphere in a permit space by a noncombustible gas (e.g. nitrogen) to such an extent that the resulting atmosphere becomes noncombustible (this procedure produces an IDLH oxygen-deficient atmosphere).

"Isolation" means the process by which a permit space is removed from service and completely protected against the release of energy and material into the space.

"Line Breaking" means the intentional opening of a pipe, line, or duct that is or has been carrying flammable, corrosive or toxic material, inert gas, or any fluid at a volume, pressure, or temperature capable of causing injury.

"Lockout or Tagout" means placing locks or tags on an energy-isolating device. Tags shall indicate that the energy-isolated device shall not be operated until the tag has been removed by the individual who affixed it.

"Permit-required confined space (Permit Space)" means a confined space that has one or more of the following:

1. Contains or has the potential to contain a hazardous atmosphere;
2. Contains a material that has the potential for engulfing an entrant;
3. Has an internal configuration such that an entrant could be trapped or asphyxiated by inwardly converging walls or by a floor which slopes downward and tapers to a smaller cross-section; or
4. Contains any other serious safety or health hazard, e.g. electrical, radioactive, moving mechanical parts, thermal, etc….

"Prohibitetia2 1/TT0 30 Tc [(m)-6(ean)-4(e)4(or)3(m(p) 0 Te 30 T(ot)0(y)20(ot)-2(t)-1)4(t)-1-

“Retrieval System”

Appendix C

C